

Specifications

the t.amp S series

MODEL	S75	S150
OUTPUT POWER STEREO 8 OHMS TA 1KHZ THD<=0.1% 4 OHMS 2 OHMS BRIDGE 8 OHMS 4 OHMS PARALEL 2 OHMS 1 OHMS	45W+45W 75W+75W 90W+90W 150W 220W 160W	85W+85W 150W+150W 200W+200W 250W 400W 320W
FREQUENCY RESPONSE	10HZ-50KHz -1.5dB	
INPUT SENSITIVITY	0.77V/26dB/1.4V	
MAXIMUM INPUT LEVEL	21dBV/9V	
INPUT IMPEDANCE ACTIVE BALANCED	20K OHMS	
SIGNAL / NOISE RATIO A - WEIGHTED RMS	>80dB	>85dB
CROSSTALK AT RATED OUTPUT POWER 8 OHM 1KHZ	>70dB	
DAMPING FACTOR f=1KHz 8 OHMS	>150	
SLEW RATE INTENAL	35V/US	40V/US
PROTECTION	SHORT CIRCUIT , CURRENT LIMITED , DC FAULT , AC LINE FUSE , LIMITER , THERMAL , CUT OFF , POWER UP/DOWN TRANSIENTS SLOW START	
INDICATORS	POWER (GREEN) •PROTECT (YELLOW) CLIP (RED) BRIDGE (GREEN) PARALLEL (GREEN)	
COOLING	WITHOUT FAN	
FRONT PANEL CONTROLS	LEVEL ACH , BCH POWER SWITCH	
REAR PANEL CONTROLS	STEREO/BRIDGED/ PARALLEL MODE SWITCH, 0.77V/26dB/1.4V INPUT SENSITIVITY SWITCH, GROUND / LIFT SWITCH	
CONNECTOR	BAL XLR INPUT, BAL 1/4" INPUT, 5 WAY BINDING POST, SPESKON	
POWER CONSUMPTION HALF POWER 8 OHMS	65W	120W
POWER SUPPLY	115V/230V 50-60HZ	
DIMENSIONS (WxDxH) mm	483 x 250 x 44	483 x 270 x 88