



The SDQ8T loudspeakers are a powerful and established value in the contractor market. The design of the cabinet is in perfect harmony with the transparent and powerful sound exhibited.

The loudspeaker comes with a U-bracket and is equipped with the 1-step protection guard to protect both woofer and tweeter from overloads. The SDQ8T can be used in both 16 Ohm or 100Volt as they come with a build-in high quality and powerful 100V transformer with several power tapings. This all makes the SDQ8T suitable for dispersion of both music and microphone calls.

The SDQ8T loudspeakers are available in black (Ref; SDQ8T-BL) and white (Ref; SDQ8T-W). As an option, the SDQ8T loudspeakers can be painted in any RAL colour (Ref; PAINT-CAB8). Please note that the minimum order quantity for PAINT-CAB8 is 12 pieces.

TECHNICAL SPECIFICATIONS

Type	2-way HiFi Pro, bass-reflex
Cabinet	Enforced poly plastic
Woofer	8" CP type
Tweeter	1.2" HD silk dome neodymium
Impedance	16 Ohm
Transfo Power Tappings	6 - 15 - 30 - 60 Watts
RMS Power 16 Ohm	
AES Rated	140 watt
Music - Program	180 watt
Dynamic Peak (lo-cut)	380 watt
Protection system	Auto-Reset 1 Guard
SPL 1 watt/1 m	94 dB
SPL Max peak	120 dB
Frequency Range	45 Hz - 20 kHz
Speaker connectors	Push terminals
Dispersion	120° H x 100° V
IP rating	40
Dimensions (H x W x D)	375 x 280 x 240 mm
Weight	5.45 Kg